



LT-S8+3 72 volt

INTRODUCING THE LT-S8+3 72 Volt

Introducing the S-SERIES 8 + 3 Seat People Mover – 72 Volt DC Motor
Designed for resorts, theme parks, nature parks and gardens, hotels and airports. In fact anywhere a quiet, stylish, convenient and efficient form of people transporter is required. The E-Car S Series 8 + 3 Seater Sightseeing Car accommodates up to eleven in comfort and a range of up to 100km. Fitted standard with a full lighting kit, hydraulic brakes, indicators & horn, windscreen and wiper, U.V. resistant metallic paint finish, mag wheels and two large side mounted rear view mirrors.

OUTSTANDING SPECIFICATIONS AND EXCEPTIONAL WARRANTY

- ☑ 10 years on the chassis,
- ☑ 3 years on electrical and mechanical components
- ☑ 2 years on batteries.

CHOICE OF GREAT COLOURS





LT-S8+3 72 Volt				
Electric system	controller	1236/300A		
	battery	US2000 batter 6V, 12units		
	motor	72V/5.5KW motor		
	charger	Computer Intelligent, input 220V/110V, ourput 72V、25A		
Charging time		Less than 12 hours （discharging rate 80%）		
Body configuration	Glass	Laminated glass	Sun Roof	Fiber glass
	seat	leather	Floor	Autiskid rubber floor
	Rear mirror	Hand operated both sides	Steering	Dual automotive-style strut and self-adjust rack-and pinion steering
	DC/Light/Signal	72V/12V-400W Front light, turning light, fog light, rear light horn, Buzzer		
	Body	“PP” alloy automatic industrial special plastic		
	Dash Board	Fiberglass dash board, Voltage Indicator 48V, Switch Head Lights, Switch - Indicators Right/Left、key switch, Switch - Forward/Reverse		
	Braking system	Front disc and rear dram, four-wheel hydraulic brake+hand brake		
	Front axle and suspension	Independent suspension, helical spring +cylinder hydraulic shock absorption		
	Rear axle and suspension	Integral type transaxle,gear ratio 12.49:1,semi-independent transaxle, spring,cylinder hydraulic shock		
	Parameter	Tire diameter	535mm	
Length*width*height		4960*1480*1960mm		
Loading passenger		14		
Max speed km/h		30km/h		
Mileage/km		80-100km （flat road）		
Max climbing ability		20%		
Mini turning radium（m）		5.5m		
Mini ground clearance		180mm		
Wheel base		Front 1180/back 1310mm		

